

## OS552 & OS552H with Auto Drop™

(Vanguard® or Honda®)

Comes with a 20" verticiling delta reel that creates the ideal environment for seed to soil contact and high germination rates. Heavy-duty infinite height adjustment for precise depth adjustment gives longer blade life than preset adjustments. It features steel guards to protect bearings and pulleys, inside engagement bail and padded handle, easy adjustable idler and premium pulleys.



“Text to Video” feature offers quick view of operating instructions on your mobile device.† Text “seeder” to 33988 US and 33433 Canada

“Text to Video” feature offers quick view of operating instructions on your mobile device.† Text “seed” to 33988 US and 33433 Canada



NOW WITH LASER CLAD BLADES FOR 3X BLADE LIFE!

## OS901SPH (Honda®)

The OS901 allows you to verticut and overseed, all in one pass! Comes standard with Honda power coupled to a self-propelled hydrostatic drive for infinite speed control that eliminates pushing and fatigue. Intuitive forward & reverse drive controls for incredibly simple operation. Its rugged design withstands the most demanding use and produces beautiful turf results.

Shown without standard seed box bonnet.

Model	Engine	Depth Adjustment*	Seeding Width	Productivity	Weight	Length	Width
OS552	205 cc Vanguard	.125" → .5" (0.3 cm → 1.3 cm)	20" slicing (51 cm)	13,200 sq.ft/hr	177 lbs (80 kg)	55" (140 cm)	26.5" (67 cm)
OS552H	162 cc Honda	.125" → .5" (0.3 cm → 1.3 cm)	20" slicing (51 cm)	13,200 sq.ft/hr	179 lbs (81 kg)	55" (140 cm)	26.5" (67 cm)
OS901SPH	270 cc Honda	.125" → (.5") (0.3 cm → 1.3 cm)	22" slicing (56 cm)	@3.0MPH 29,040 ft <sup>2</sup> /hour 0.67 acre/hr	323 lbs (146.5 kg)	58.38" (148 cm)	30.75" (78 cm)

† Data rates may apply.

\*With up to an additional 1/2 inch (1.3 cm) of adjustment for blade wear.

## OS552 Features/Benefits



**25 lb front mounted poly seed box** with on-board customer instructions to help set drop rates for various seed. The box and agitator bar won't rust or dent – standard on the overseeder.



**Heavy-duty wheels** with steel rim and roller bearings stand up to the most demanding customers and applications.



**Auto Drop™ system** is easy to adjust, with drop rates for a variety of seeds listed in on-board instructions.




**Fold-n-Go™ no tool, no bolt foldable handle** with inside bail and padded handles. Great for comfort, storage, transport and long life. (PR550 unit shown).


## OS901 Features/Benefits/Accessories



**Fold-n-Go™ no tool, no bolt foldable handles** are great for storage, transport and long life.




**Self-propelled hydrostatic drive** with intuitive forward & reverse drive controls eliminate pushing to reduce fatigue. Simple auto release switch for transport in off position.



**Auto Drop™ system** automatically starts and stops seed drop with reel engagement & disengagement, conserving valuable seed. **Spring loaded stainless steel slide** prevents binding if clogging occurs and is easy to clean. Spring loaded hardware eliminates corrosion.




**Elevated seed box** prevents moisture from clogging the seed drop & provides excellent visibility. Axle driven seed agitator eliminates belts & tire-on-tire systems.



**Foot pedal** for operator ease of use and improved blade depth and wear. Standard on OS901. Retro Kit available for older OS900 Series. (Part No. 351611)



**Blade design plus laser cladding** provides improved slicing, reduced thatch pick-up and longer life due to sharpened leading edge, design, attack angle and new height adjust. Standard. (Part No. 351290)



**Floating cutting head** with an exclusively designed 22" (56 cm) slicing reel floats with contours of yards, increasing seed to soil contact & improving germination rates.



**Clear Seed Box Bonnet**  
Standard (Part No. 351617)

**Optional Sulky**  
(Part No. 351601)

