

# SOD CUTTERS



SC121H

## SC121H

(Honda®)

There's simply no sod cutter that's easier to use. Just set the depth, shift into gear, engage the blade, start the drive and you're off! Great for small projects and easy to transport. 12" cutting width and up to 1.38" deep. Make sure the ground is soft and wet before using. 3-year limited engine warranty.\*\*

**WEIGHS ONLY 161 LBS!**

Text "cut" to 33988 US or 33433 Canada\*



SC181H

## SC181H, SC181HG, SC181HEU & SC240HG Hydro-Drive

(Honda®)

## SC181K, SC181KG & SC240KG Hydro-Drive

(Kohler® Available late 2023)

The Hydro-Drive 18" and 24" sod cutters are built upon the most rugged foundation in the industry with a superstructure frame that features 50 additional pounds of steel and supports a heavy-duty drive and cut system with a laser clad cutting blade - for the ultimate in smooth, precise cutting and 3x blade life. Because it is simple to use and easy to set, the 18" unit is a favorite for irrigation, landscape, hardscape, sports field and flatwork, while the 24" is ideal for taking the chore out of large tear-out or removal projects. Knobby tires on the SC181HG, SC240HG, SC181KG and SC240KG are ideal for softer touch, shallow cut, bent grass applications. A Honda 5.5 gross HP† engine powers the 18" model (2-year limited warranty\*\*) and 6.5 gross HP† Honda engine powers the 24" model (2-year limited residential and 1-year limited commercial warranty\*\*). 9.5 foot-pounds of torque powers the Kohler-powered models (3-year limited warranty\*\*) available late 2023. (The Honda-powered SC181HEU is specified for European customers.) See the SC181 series video at Billygoat.com.



SC240KG Kohler engine models available late 2023.

**Billy Goat® Controls**  
The Common Experience™

Text "sod" to 33988 US or 33433 Canada\*

MODEL	ENGINE	WEIGHT	CUTTING WIDTH	CUTTING DEPTH	LENGTH	WIDTH	HEIGHT	TRANSMISSION
SC121H	163 cc Honda GX160	165 lb. (74 kg)	12" (31 cm)	Maximum of 1.38" (3.5 cm)	31" (78 cm)	16.5" (42 cm)	31" (78 cm)	2 forward speeds
SC181H	163 cc Honda GXV160	395 lb. (179 Kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
SC181HG	163 cc Honda GXV160	395 lb. (179 Kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
SC181HEU	163 cc Honda GXV160	406 lb. (184 Kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
***SC182HCA††	187 cc Honda GSV190	395 lb. (179 Kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
SC181K†	200 cc Kohler COMMAND PRO CV200	397 lb. (180 kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
SC181KG†	200 cc Kohler COMMAND PRO CV200	397 lb. (180 kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
SC181KEU††	200 cc Kohler COMMAND PRO CV200	400 lb. (181 kg)	18" (45.7 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
***SC240HG††	187cc Honda GSV190	403 lb. (183 kg)	24" (60.9 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310
SC240KG††	200 cc Kohler® COMMAND PRO CV200	414 lb. (187.7 kg)	24" (60.9 cm)	Max 2.5" (6.35 cm)	60" (1,524 mm)	26.5" (673 mm)	38.5" (978 mm)	Hydro-Gear® RT310

\*Data rates may apply.

\*\*See operator's manual for warranty details.

\*\*\*Limited availability.

†Power rated by engine manufacturer.

††Compliant in CA.

Kohler engine models available late 2023

Not all units are CA approved. See your dealer.



## SC121H FEATURES / BENEFITS



**Ergonomic control levers** control cut and drive system.



**Durability**  
Rugged frame is isolated with 6 rubber mounts for reduced vibration and smooth handling.

**Balanced 4-point footprint** for added stability & ease of use vs. 3-point styles.



**Rear wheel drive**  
Geared transmission with 2 forward speeds. Rear tractor tires for added traction. Use low gear for cutting and faster gear for transport.



**One-step cut adjustment** changes cutting depth by moving a single lever.

## SC181H, SC240HG & SC240KG FEATURES / BENEFITS



**Set and Forget™ blade depth adjustment to 2.5"**  
Single lever and clamp at operator's position adjusts simply, saving time and providing precise cutting depths.



**Well vented housing** provides increased venting for cool operation, plus three easy-access service doors located at front, center and back of machine.



**Superstructure frame** features a 3/8" thick steel substructure and 1/2" thick steel lateral support for reinforced frame rigidity.



**Kohler engine** includes cyclonic air filter for extended replacement intervals. Available in late 2023.



**Rear swivel caster**  
Perfect for curved work or making turns at the end of a pass. Locks for straight cutting.



**Standardized controls** offer same intuitive variable speed, fingertip, hydro-drive controls as found on the Billy Goat hydro-drive brushcutter, 25" aerator, overseeder, as well as the new post hole auger.



**A) Durable cut system** features rugged cast iron gear box, spiral cut gears and thick seals. Laser clad cutting blade for precise cut & up to 3x blade life.

**B) St. Augustine blade.** Sharpened inside arm corners. Optional. For SC181 and SC182 ser. only. (Part No. 373333)



**A) Unique DRIVE Wheels**  
Paddle-style for landscape applications; SC181H model. Designed to shed mud in wet conditions and grip in dry for improved cutting in all conditions.



**B) Knobby Wheels for Golf Applications** SC181HG, SC240HG and SC240KG models. Ideal for softer touch, bent grass, shallow cut applications. SC181HG (Part No. 373321); SC240HG and SC240KG (Part No. 373334). Kohler engine models available in late 2023.