

# AIR / WATER HOSE

## 1502 – RED EPDM RUBBER

### ASSEMBLIES WITH UNIVERSAL COUPLINGS



SIZE (ID)	ITEM NUMBER	COLOR	PSI RATING*
1/2"	1502-50X50R	RED	300
3/4"	1502-75X50R	RED	300
3/4"	1502M-75X50R	RED	200
3/4"	1502-75X50Y	YLW	300
3/4"	1502-75X50B	BLUE	300
1"	1502-1X50R	RED	300
1"	1502M-1X50R	RED	200

\* PRESSURE RATING LISTED ABOVE IS THE HOSE RATING ONLY  
ASSEMBLIES WITH UNIVERSAL COUPLINGS ARE RATED AT 150 PSI

### ASSEMBLIES WITH M NPT BRASS COUPLINGS



SHOWN WITH OPTIONAL  
QUICK CONNECT COUPLINGS

HOSE SIZE (ID)	THREAD SIZE (NPT)	ITEM NUMBER
1/4"	1/4"	1502-25X50MM
3/8"	1/4"	1502-38X50-04M
3/8"	3/8"	1502-38X50-06M
1/2"	1/2"	1502-50X50MM

50 FT ASSEMBLIES LISTED - 25 & 100 FT LENGTHS AVAILABLE

**ALWAYS USE SAFETY CABLES TO SECURE AIR HOSE**

REELS MAY NOT BE CONTINUOUS

### BULK HOSE

-40 TO +212 DEG F



ARPM CLASS C OIL RESISTANT TUBE  
(OIL MISTED AIR ACCEPTABLE)

PSI RATING IS FOR THE BULK HOSE ONLY  
ASSEMBLY PRESSURE VARIES BASED ON  
COUPLING AND CLAMP TYPE

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT	FT / REEL
1/4"	1502-25	300	0.12	800
3/8"	1502-38	300	0.16	700
1/2"	1502-50	300	0.25	500
5/8"	1502-63	300	0.35	450
3/4"	1502-75	300	0.38	400
1"	1502-100	300	0.52	300
1-1/4"	1502-125	200	0.80	250
1-1/2"	1502-150	200	0.90	200
2"	1502-200	200	1.20	250

200 PSI VERSION AVAILABLE ALL SIZES

# AIR / WATER HOSE

## 1503 – NITRILE OIL RESISTANT RUBBER

-40 TO +212 DEG F

**OIL RESISTANT / NON-CONDUCTIVE**



SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FT	SPOOL LGTH
1/4"	1503-25	300	0.12	800'
3/8"	1503-38	300	0.18	650'
1/2"	1503-50	300	0.26	500'
3/4"	1503-75	300	0.40	400'
1"	1503-100	300	0.56	300'

REELS MAY NOT BE CONTINUOUS

*NOT FOR REFINED FUEL APPLICATIONS  
INQUIRE FOR FUEL & OIL DELIVERY HOSE*

## 1509 – PUSH LOCK RUBBER

-40 TO +212 DEG F

**OIL RESISTANT / HIGHLY FLEXIBLE**



SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FT	SPOOL LGTH
1/4"	1509_-25	300	0.10	700'
3/8"	1509_-38	300	0.12	700'
1/2"	1509_-50	300	0.16	600'
5/8"	1509_-63	300	0.22	500'
3/4"	1509_-75	300	0.30	400'

AVAILABLE IN BLACK, BLUE,  
RED, GREEN & GRAY  
REELS MAY NOT BE CONTINUOUS

COMPATIBLE WITH B20\*, DIESEL, ETHANOL & GASOLINE  
(NOT FOR FUEL DISPENSING APPLICATIONS)  
\*IN DEDICATED SERVICE

### PUSH LOCK HOSE COUPLINGS

NO HOSE CLAMP OR FERRULE IS REQUIRED WHEN ASSEMBLING PUSH LOCK HOSE  
WITH THESE SPECIALLY DESIGNED PUSH LOCK COUPLINGS

CUT HOSE STRAIGHT AND PRESS FITTING IN COMPLETELY UP TO YELLOW RING



**MALE NPT RIGID & SWIVEL**  
MALE SAE / JIC THREAD  
MALE NPT 90° ELBOW



**HOSE TO HOSE MENDER**  
JUMP SIZES AVAILABLE



**FEMALE NPSM SWIVEL**  
FEMALE NPT RIGID  
FEMALE SAE / JIC

GARDEN THREAD M & F NOW AVAILABLE

DO NOT USE A CLAMP WITH THESE FITTINGS, THE SPECIAL SERRATIONS WILL CUT INTO THE HOSE WALL

# AIR / WATER HOSE

## 1803 – WIRE BRAID / BULL AIR

### ASSEMBLIES WITH UNIVERSAL QUICK CONNECT COUPLINGS



ASSEMBLIES WITH UNIVERSAL COUPLINGS  
ARE RATED FOR 150 PSI

3/4" X 50'	1803-75X50UB
1" X 50'	1803-1X50UB
1-1/2" X 50'	1803-150X50UB
2" X 50'	1803-2X50UB

2-LUG COUPLING DESIGN THROUGH 1" HOSE ID  
ASSEMBLIES OVER 1" HAVE 4-LUG COUPLING DESIGN  
2-LUG AND 4-LUG COUPLINGS ARE NOT COMPATIBLE  
25 & 100 FT LENGTHS ALSO AVAILABLE

### ASSEMBLIES WITH MALE NPT & FEMALE GROUND JOINT COUPLINGS



FEMALE GROUND JOINT COUPLING  
INCLUDES FEMALE NPT SPUD ADAPTER  
DOUBLE SPUD & M NPT SPUD ALSO AVAILABLE

3/4" X 50'	1803-75X50MFGJ
1" X 50'	1803-1X50MFGJ
1-1/2" X 50'	1803-150X50MFGJ
2" X 50'	1803-2X50MFGJ
3" X 50'	1803-3X50MFGJ
4" X 50'	1803-4X50MFGJ

FEMALE GROUND JOINT EACH END = FFGJ  
25 & 100 FT LENGTHS ALSO AVAILABLE

**ALWAYS USE SAFETY CABLES TO SECURE AIR HOSE**

100 FT MAX ROLL LENGTH

**BULK HOSE**

-25 TO +200 DEG F

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
1/2"	1803-50	600	0.40
3/4"	1803-75	600	0.65
1"	1803-100	600	0.85
1-1/4"	1803-125	600	1.10
1-1/2"	1803-150	600	1.30

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT
2"	1803-200	600	1.90
2-1/2"	1803-250	600	2.50
3"	1803-300	600	3.30
4"	1803-400	600	4.75
6"	1803-600	600	6.89

TEXTILE BRAID VERSION (NO WIRE) ALSO AVAILABLE – TYPE 1801

HIGH-TEMP VERSION (+275 DEG F) AVAILABLE IN SELECT SIZES – TYPE 1803H

**HIGH PRESSURE HOSE WHIP RESTRAINTS AVAILABLE**

PSI RATING LISTED IS THE RECOMMENDED MAX OPERATING PRESSURE OF THE BULK HOSE ONLY  
ASSEMBLY PRESSURE WILL VARY BASED ON SIZE AND FITTING TYPE


# AIR / WATER HOSE

## 1522 – BLACK EPDM RUBBER

### ASSEMBLIES WITH BRASS MXF GHT COUPLINGS



**HOT WATER SERVICE APPROVED  
STAYES FLEXIBLE IN COLD WEATHER**



**CRUSH-PROOF HD BRASS COUPLINGS  
CUSTOM CONFIGURATIONS AVAILABLE**

**MD GRADE HOSE IS 125 PSI WITH  
NICKLE PLATED BRASS GHT FITTINGS**

### 5/8" HOSE ASSEMBLIES

5/8" X 25'	1522-63X25GHT
5/8" X 50'	1522-63X50GHT
5/8" X 100'	1522-63X100GHT

### 3/4" HOSE ASSEMBLIES

3/4" X 25'	1522-75X25GHT
3/4" X 50'	1522-75X50GHT
3/4" X 100'	1522-75X100GHT

### 1" HOSE ASSEMBLIES

1" X 50'	1522-1X50GHT
1" X 50'	1522-1X50MF

MF = NPSH STRAIGHT THREAD

### MD GRADE WATER HOSE

5/8" X 50'	1521-63X50GHT
3/4" X 50'	1521-75X50GHT

REELS MAY NOT BE CONTINUOUS

### BULK HOSE

-40 TO +212 DEG F



CUT LENGTHS AVAILABLE

**PSI RATING IS FOR THE BULK HOSE ONLY  
ASSEMBLY PRESSURE VARIES BASED ON  
COUPLING AND CLAMP TYPE**

SIZE (ID)	ITEM NUMBER	PSI RATING	LBS / FOOT	FT / REEL
1/4"	1522-25	200	0.10	800
3/8"	1522-38	200	0.16	700
1/2"	1522-50	200	0.22	500
5/8"	1522-63	200	0.26	450
3/4"	1522-75	200	0.34	400
1"	1522-100	200	0.45	300
1-1/4"	1522-125	200	0.78	250
1-1/2"	1522-150	200	0.86	200
2"	1522-200	200	1.20	250

# AIR / WATER HOSE

## 8030 – PRESSURE WASHER ASSEMBLIES



**1-WIRE HOSE  
3000 PSI ASSEMBLIES**



**2-WIRE HOSE  
6000 PSI ASSEMBLIES**

3/8" X 50'	8030-38X50MMS
3/8" X 100'	8030-38X100MMS

3/8" X 50'	8030-6000X50MMS
3/8" X 100'	8030-6000X100MMS

**OIL RESISTANT NON-SLIP FABRIC IMPRESSION COVER**

**WIRE BRAID SPECIALLY DESIGNED FOR IMPULSE AND FLEXING**

**ASSEMBLIES INCLUDE 3/8 MALE NPT EACH END (ONE SIDE SWIVEL) WITH BEND RESTRICTORS  
CUSTOM LENGTH ASSEMBLIES AND BULK SPOOLS AVAILABLE**

### COUPLER (BRASS)

SIZE	PART #	MAX PSI
1/4"	STFC2	5500
3/8"	STFC3	4500
1/2"	STFC4	3500
3/4"	STFC6	3100



### QC PLUG

SIZE	PART #	BRASS PSI	STEEL PSI
1/4"	STFP2(B)	3800	5500
3/8"	STFP3(B)	2700	4500
1/2"	STFP4(B)	2200	3500
3/4"	STFP6(B)	1700	3100

ALSO AVAILABLE IN 303 SS (MOST SIZES AND STYLES)

## SEWER & DRAIN JETTING HOSE



SIZE (ID)	GREEN	RED	BLACK	ORANGE	BLUE
1/4"	4000#	5000#	-	-	-
3/8"	4000#	5000#	-	-	-
1/2"	4000#	5000#	4000#	-	3000#
5/8"	-	-	4000#	2500#	-
3/4"	-	-	-	2500#	3000#
1"	-	-	-	2500#	3000#

**HOSE WITH POLYURETHANE COVER & HIGH TENSILE SYNTHETIC FIBER BRAID  
DESIGNED TO SLIDE EASILY FOR SEWER, DRAIN & LATERAL LINE CLEANING**

LONG LENGTH ASSEMBLIES • EXTRA SLICK COVER OPTION AVAILABLE  
• NOT FOR HOT WATER CLEANING APPLICATIONS